

نوع		ظرفیت 20 ساعته (AH)	ظرفیت ذخیره RC (min)	جریان راه اندازی سرد CCA EN (A)	ماکزیمم ابعاد باتری (mm)				نوع و پایه جعبه	نوع قطب	جانمایی قطب
جعبه	کد باتری				طول	عرض	ارتفاع	ارتفاع کلی			
DIN		Sealed Maintenance Free									
L1	SMFL105047021L	50	79	470	207	175	189	189	B3	A1	0
	SMFL105047021R	50	79	470	207	175	189	189	B3	A1	1
L2	SMFL205047021L	50	79	415	242	175	188	188	B3	A1	0
	SMFL205047021R	50	79	415	242	175	188	188	B3	A1	1
	SMFL205550521L	55	88	470	242	175	188	188	B3	A1	0
	SMFL205550521R	55	88	470	242	175	188	188	B3	A1	1
	SMFL206056021L	60	98	500	242	175	188	188	B3	A1	0
	SMFL206056021R	60	98	500	242	175	188	188	B3	A1	1
L3	SMFL306659521L	66	110	600	277	175	189	189	B3	A1	0
	SMFL306659521R	66	110	600	277	175	189	189	B3	A1	1
	SMFL307266021L	72	122	660	277	175	189	189	B3	A1	0
	SMFL307266021R	72	122	660	277	175	189	189	B3	A1	1
L5	SMFL509083021L	90	154	830	349	175	189	189	B3	A1	0
	SMFL509083021R	90	154	830	349	175	189	189	B3	A1	1
	SMFL510092021L	100	179	920	349	175	189	189	B3	A1	0
	SMFL510092021R	100	179	920	349	175	189	189	B3	A1	1
JIS		Sealed Maintenance Free									
B20	SMFB2003530523L	35	52	305	197	128	202	222	N	A2	0
	SMFB2003530523R	35	52	305	197	128	202	222	N	A2	1
B24	SMFB2404538021L	45	70	380	238	128	202	222	N	A1	0
	SMFB2404538021R	45	70	380	238	128	202	222	N	A1	1
	SMFB2404538023L	45	70	380	238	128	202	222	N	A2	0
	SMFB2404538023R	45	70	380	238	128	202	222	N	A2	1
D23	SMFD2306052021L	60	98	520	238	178	204	223	B4	A1	0
	SMFD2306052021R	60	98	520	238	178	204	223	B4	A1	1
	SMFD2306656021L	66	110	560	238	178	204	223	B4	A1	0
	SMFD2306656021R	66	110	560	238	178	204	223	B4	A1	1
D26	SMFD2607062021L	70	118	620	256	176	204	224	B4	A1	0
	SMFD2607062021R	70	118	620	256	176	204	224	B4	A1	1
	SMFD2607566021L	75	128	660	256	176	204	224	B4	A1	0
	SMFD2607566021R	75	128	660	256	176	204	224	B4	A1	1
D31	SMFD3107062021L	70	118	620	306	175	204	225	B4	A1	0
	SMFD3107062021R	70	118	620	306	175	204	225	B4	A1	1
	SMFD3108066021L	80	138	660	306	175	204	225	B4	A1	0
	SMFD3108066021R	80	138	660	306	175	204	225	B4	A1	1
	SMFD3109076021L	90	158	760	306	175	204	225	B4	A1	0
	SMFD3109076021R	90	158	760	306	175	204	225	B4	A1	1
	SMFD3110086021L	100	179	860	306	175	204	225	B4	A1	0
	SMFD3110086021R	100	179	860	306	175	204	225	B4	A1	1
G51	SMFG5115010121R	150	290	1020	510	222	209	231	B8	A1	3
	SMFG5115010121L	150	290	1020	510	222	209	231	B8	A1	4
	SMFG5117011321R	170	336	1100	510	222	209	231	B8	A1	3
	SMFG5117011321L	170	336	1100	510	222	209	231	B8	A1	4
	SMFG5118012121R	180	360	1140	510	222	209	231	B8	A1	3
	SMFG5118012121L	180	360	1140	510	222	209	231	B8	A1	4
	SMFG5119012621R	190	383	1160	510	222	209	231	B8	A1	3
	SMFG5119012621L	190	383	1160	510	222	209	231	B8	A1	4
H51	SMFH5120010521R	200	407	1160	511	278	216	238	B8	A1	3
	SMFH5120010521L	200	407	1160	511	278	216	238	B8	A1	4
	SMFH5122011021R	220	456	1200	511	278	216	238	B8	A1	3
	SMFH5122011021L	220	456	1200	511	278	216	238	B8	A1	4
	SMFH5123011511R	230	481	1240	511	278	216	238	B8	A1	3
	SMFH5123011511L	230	481	1240	511	278	216	238	B8	A1	4
	SMFH5124012011R	240	505	1260	511	278	216	238	B8	A1	3
	SMFH5124012011L	240	505	1260	511	278	216	238	B8	A1	4

نوع		ظرفیت 20 ساعته	ظرفیت ذخیره RC (min)	جریان راه اندازی سرد CCA EN (A)	ماکزیمم ابعاد باتری (mm)				نوع و پایه جعبه	نوع قطب	جانمایی قطب
جعبه	کد باتری	(AH)		(A)	طول	عرض	ارتفاع	ارتفاع کلی			
DIN Low Maintenance											
L1	L105047021L	50	79	470	207	175	189	189	B3	A1	0
	L105047021R	50	79	470	207	175	189	189	B3	A1	1
L2	L205047021L	50	79	415	242	175	187	187	B3	A1	0
	L205047021R	50	79	415	242	175	187	187	B3	A1	1
	L205550521L	55	88	470	242	175	187	187	B3	A1	0
	L205550521R	55	88	470	242	175	187	187	B3	A1	1
	L206056021L	60	98	500	242	175	187	187	B3	A1	0
	L206056021R	60	98	500	242	175	187	187	B3	A1	1
L3	L306659521L	66	110	600	277	175	189	189	B3	A1	0
	L306659521R	66	110	600	277	175	189	189	B3	A1	1
	L307266021L	72	122	660	277	175	189	189	B3	A1	0
	L307266021R	72	122	660	277	175	189	189	B3	A1	1
L5	L509083021L	90	154	830	349	175	189	189	B3	A1	0
	L509083021R	90	154	830	349	175	189	189	B3	A1	1
	L510092021L	100	179	920	349	175	189	189	B3	A1	0
	L510092021R	100	179	920	349	175	189	189	B3	A1	1
JIS Low Maintenance											
D23	D2306052021L	60	98	520	238	178	204	223	B4	A1	0
	D2306052021R	60	98	520	238	178	204	223	B4	A1	1
	D2306656021L	66	110	560	238	178	204	223	B4	A1	0
	D2306656021R	66	110	560	238	178	204	223	B4	A1	1
D31	D3107062021L	70	118	620	306	175	204	225	B4	A1	0
	D3107062021R	70	118	620	306	175	204	225	B4	A1	1
	D3108066021L	80	138	660	306	175	204	225	B4	A1	0
	D3108066021R	80	138	660	306	175	204	225	B4	A1	1
	D3109076021L	90	158	760	306	175	204	225	B4	A1	0
	D3109076021R	90	158	760	306	175	204	225	B4	A1	1
	D3110086021L	100	179	860	306	175	204	225	B4	A1	0
	D3110086021R	100	179	860	306	175	204	225	B4	A1	1
E41	E4110086021L	100	179	860	413	177	203	223	B8	A1	0
	E4111092021L	110	201	920	413	177	203	223	B8	A1	0
	E4112010221L	120	223	1020	413	177	203	223	B8	A1	0
G51	G5115010121R	150	290	1020	510	222	192	215	B8	A1	3
	G5115010121L	150	290	1020	510	222	192	215	B8	A1	4
	G5117011321R	170	336	1100	510	222	192	215	B8	A1	3
	G5117011321L	170	336	1100	510	222	192	215	B8	A1	4
	G5118012121R	180	360	1140	510	222	192	215	B8	A1	3
	G5118012121L	180	360	1140	510	222	192	215	B8	A1	4
	G5119012621R	190	383	1160	510	222	192	215	B8	A1	3
	G5119012621L	190	383	1160	510	222	192	215	B8	A1	4
H51	H5120010521R	200	407	1160	511	278	216	238	B8	A1	3
	H5120010521L	200	407	1160	511	278	216	238	B8	A1	4
	H5122011021R	220	456	1200	511	278	216	238	B8	A1	3
	H5122011021L	220	456	1200	511	278	216	238	B8	A1	4
	H5123011511R	230	481	1240	511	278	216	238	B8	A1	3
	H5123011511L	230	481	1240	511	278	216	238	B8	A1	4
	H5124012011R	240	505	1260	511	278	216	238	B8	A1	3
	H5124012011L	240	505	1260	511	278	216	238	B8	A1	4

